

MODEL VO5005



Captures Digital Still and Video

SPECIFICATIONS

SPECIFICATIONS	
IMAGE SENSOR	CMOS, 5 megapixels (2592 x 1944), sensor area 1/ 1.8"
LENS	F 2.8, f = 8.8 mm, View Angle 52°, 5 – element glass lens
IMAGE QUALITY	5 megapixels
FOCUS	Normal:1.5m to Infinity, Macro: 50cm
SHUTTER	Automatic
WHITE BALANCE	Automatic w/presets for automatic, daylight, cloudy, fluorescent lamp and tungsten lamp
EXPOSURE	Automatic and Manual (+/- 2EV)
INTERNAL MEMORY	16MB SDRAM (Not For Storage)
EXTERNAL MEMORY	Accepts Secure Digital (SD) Memory Cards (card not included)
STORAGE CAPACITY STILL MODE	L (10M): 3628 x 2721 Pixels M (5M): 2588 x 1941 Pixels S (3M): 2044 x 1533 Pixels
STORAGE CAPACITY MOVIE MODE	Video: QVGA 320 x 240 Pixels (20 fps) SD Card not included. No audio function
VIDEL CAMERA MODE FRAME RATE	VGA 640 x 480 Pixels QVGA 320 x 240 Pixels
FLASH	Force-on, Force-off, and Auto
LCD DISPLAY	2.0"TFT LCD
SELF-TIMER	2-Second and 10-Second delay
COMPRESSION	JPEG, MJPEG (AVI)
INTERFACE	USB 1.1
VIDEO OUTPUT	No
RTC (REAL-TIME CLOCK)	Yes
Power Saver	Auto power-off: 60 sec.
Power	2 AAA Alkaline batteries (included)
Operating System	Microsoft Windows 98SE / 2000 / ME / XP Support Image Download for RedHat Linux 8.0 and MAC OS 9 or Later
Software Included	ArcSoft PhotoImpression 5.0 VideoImpression 2.0
Dimensions	3.52″ x 2.28″ x 0.79″ (89.5 x 58 x 20mm)

Specifications are subject to change without notice. $\ensuremath{\mathbb{C}}$ 2006 VistaQuest Corporation

5 Megapixel Digital Camera w/ 2.0" Color TFT LCD Display

> Captures Digital Still and Video

- 5.0 Megapixels
- 4x Digital Zoom
- Automatic Flash
- 2.0" Color TFT LCD Display
- Accepts Secure Digital (SD) Memory Cards (Not Included)
- MAC/PC & Linux 8.0 Compatible



VistaQuest Corporation, 6303 Owensmouth Avenue, 10th Floor, Woodland Hills, CA 91367-2262 Tel 818.936.3474 • Fax 818.936.2706 • www@vistaquestusa.com